

# 150kVA Soundproof Generator

## Features

- ☛ Noise Level @ 1m, 74dBA (@7m, 62dBA)
- ☛ Autostart DSE CP with MCCB
- ☛ VELCB
- ☛ Micro Switch Protection over Buss Bar Door
- ☛ Oil Extraction Pump
- ☛ 3 Way Fuel Valve
- ☛ Battery Isolator
- ☛ Water Separator Std
- ☛ Cental Lifting Hook
- ☛ Fork Lift Pockets
- ☛ Fully Bunded - c/w bund alarm
- ☛ Remote Telemetry - c/w External Fuel Level Monitoring
- ☛ 50 Hz/60 Hz Selector Switch
- ☛ Bulk Fuel Tank Connectors
- ☛ Battery Charger

Generating Set	50 Hz	60 Hz
Continuous Power	150 kVA	190 kVA
Standby Power	165 kVA	209 kVA
Noise Level @ 1m / 7m	75 dBA / 63 dBA	
Power Factor	cos ! 0.8	
Continuous Power	120 kWe	158 kWe
Standby Power	132 kWe	174 kWe
Amps 3 Phase	208 A	
Fuel consumption 70% load	22.4 l/h	28.4 l/h
Engine	1500 rpm	
Model	NEF67TM4	
Continuous Power	130 kWm	
Standby Power	143.8 kWm	
Aspiration	Turbocharged	
Cooling System	Water	
Speed Governor	Electronic	
Cylinder Number	6	
Displacement	6,800 cm <sup>3</sup>	
Logistic Information	GX170F	
Fuel Tank	400 ltr	
Weight (Wet)	2,860 kg	
Dimensions (L x W x H)	335 x 110 x 217 cm	
Control Panel	DSE 8610	
Auto Start	Standard	

CES Power has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.