

# 250kVA Soundproof Generator

## Features

- 🔌 Noise Level @ 1m, 75dBA (@7m, 63dBA)
- 🔌 Autostart DSE CP with MCCB
- 🔌 VELCB
- 🔌 Micro Switch Protection over Buss Bar Door
- 🔌 Oil Extraction Pump
- 🔌 3 Way Fuel Valve
- 🔌 Battery Isolator
- 🔌 Water Separator Std
- 🔌 Cental Lifting Hook
- 🔌 Fork Lift Pockets
- 🔌 Fully Bunded - c/w bund alarm
- 🔌 Remote Telemetry - c/w External Fuel Level Monitoring
- 🔌 Battery Charger
- 🔌 Bulk Fuel Tank Connectors

Generating Set	50 Hz	60 Hz
Continuous Power	250 kVA	289 kVA
Standby Power	275 kVA	318 kVa
Noise Level @ 1m / 7m	75 dBA / 63 dBA	
Power Factor	cos ! 0.8	
Continuous Power	200 kWe	240 kWe
Standby Power	220 kWe	265 kWe
Amps 3 Phase	347 A	
Fuel consumption 70% load	46 l/h	54 l/h
Engine	1500 rpm	
Model	Cummins QSL9G3	
Continuous Power	217 kWm	
Standby Power	239 kWm	
Aspiration	Turbocharged	
Cooling System	Water	
Speed Governor	Electronic	
Cylinder Number	6	
Displacement	8,700 cm <sup>3</sup>	
Logistic Information	GQ275C	
Fuel Tank	450 ltr	
Weight (Wet)	3,900 kg	
Dimensions (L x W x H)	380 x 120 x 230 cm	
Control Panel	DSE 8610	
Auto Start	Standard	

CES Power has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.