

300kVA Soundproof Generator

Features

-  Noise Level @ 1m, 76dBA (@7m, 64dBA)
-  Autostart DSE CP
-  Motorised MCCB rated at 630A
-  VELCB
-  Micro Switch Protection over Buss Bar Door
-  Oil Extraction Pump
-  3 Way Fuel Valve
-  Battery Isolator
-  Water Separator Std
-  Cental Lifting Hook
-  Fork Lift Pockets
-  Fully Bunded - c/w bund alarm
-  Remote Telemetry - c/w External Fuel Level Monitoring
-  Battery Charger
-  Bulk Fuel Tank Connectors

Generating Set	50 Hz	60 Hz
Continuous Power	301 kVA	340 kVA
Standby Power	346 kVA	392 kVA
Noise Level @ 1m / 7m	75 dBA / 63 dBA	
Continuous Power	250 kW _e	280 kW _e
Standby Power	288 kW _e	326 kW _e
Amps 3 Phase	417 A	
Fuel consumption 70% load	46 l/h	55 l/h
Engine	1500 rpm	1800 rpm
Model	Cummins QS L9G7	
Continuous Power	268 kW _m	307 kW _m
Standby Power	314 kW _m	356 kW _m
Aspiration	Turbocharged	
Cooling System	Water	
Speed Governor	Electronic	
Cylinder Number	6	
Displacement	8,800 cm ³	
Logistic Information	GX331C	
Fuel Tank	450 ltr	
Weight (Wet)	4,030 kg	
Dimensions (L x W x H)	383 x 123 x 221 cm	
Control Panel	Deep Sea 7510 or 8610?	
Auto Start	Standard	

CES Power has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.