

40kVA Soundproof Generator

Features

- Stage IIIA
- Noise Level @ 1m, 73dBA (@7m, 61dBA)
- Autostart DSE CP with MCCB
- VELCB
- Micro Switch Protection over Buss Bar Door
- Oil Extraction Pump
- 3 Way Fuel Valve
- Battery Isolator
- Water Separator Std
- Central Lifting Hook
- Fork Lift Pockets
- Fully Bunded - c/w bund alarm
- Remote Telemetry - c/w External Fuel Level Monitoring
- Bulk Fuel Tank Connectors
- Battery Charger

| Generating Set | | 50 Hz |
|---------------------------|--|-----------------------|
| Continuous Power | | 40 kVA |
| Standby Power | | 44 kVA |
| Noise Level @ 1m / 7m | | 73 dBA / 61 dBA |
| Power Factor | | cos ! 0.8 |
| Continuous Power | | 33 kW _e |
| Standby Power | | 36 kW _e |
| Amps 3 Phase | | 55 A |
| Fuel consumption 70% load | | 6.6 l/h |
| Engine | | 1500 rpm |
| Model | | NEF45AMIA |
| Continuous Power | | 36 kW _m |
| Standby Power | | 40 kW _m |
| Aspiration | | Turbocharged |
| Cooling System | | Water |
| Speed Governor | | Mechanical |
| Cylinder Number | | 4 |
| Displacement | | 2,900 cm ³ |
| Logistic Information | | GX52F |
| Fuel Tank | | 135 ltr |
| Weight (Wet) | | 1,155 kg |
| Dimensions (L x W x H) | | 196 x 98 x 148 cm |
| Control Panel | | DSE 7310 |
| Manual Start | | Standard |

CES Power has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.

